
ELGAR

14335813 ELGAR 70 B2C S 450 275-827 CRS MR Vertical wall light fitting with flux turned to the ground



Description

- ELGAR Vertical wall light fitting with flux turned to the ground
- Internal anodized finishing aluminum gear unit cover: SILVER
- Housing: UV-resistant co-extruded polycarbonate/PMMA for inside/outside use
- End caps & fixing straps: Stainless steel 316L
- Longitudinal louvre in scratch brushed silver aluminium with inclined lamina
- External metal parts in 316L stainless steel and screws in A4 stainless steel
- Internal grey lacquered steel gear tray RAL 9006
- Gaskets: Gaskets moulded in EPDM



Light specifications and controlling


- High-efficiency removable LED modules (IRC>80, 3 SDCM)
- Luminous flux: 275 lm
- Colour temperature: 2700 K
- Specific satin-finish primary diffuser optic
- · Reversible longitudinal louvre
- Constant Current Driver (non-dimmable)



 Cable entry with nickel-coated brass cable gland for cable Ø 8 - 12 mm

Installation and maintenance

- Provided with 1m 3G1,5 cable with tinned copper meshwork under transparent tubing
- Connection to 2x2.5mm² automatic terminal block
- 2 reinforced fixing straps in stainless steel with variable centre distance and allowing 360° orientation
- Opening and closing by tightening the nut on the cable gland
- Provided with stainless steel cable plate 316L, for indoor use (IP 40), for earthing
- Installation vertical: position cable gland positioned downwards
- Easily removable LED modules and driver

















Characteristics

• Warranty: 5 years

• 50 000 h L80/B10 at 25°C

 \bullet Operating temperature: -20 °C to +35 °C

• Imperviousness: IP66, IP68 and IP69K

Resistance to IK shocks: IK10

• Electrical class: Class II

• Power supply: 220-240 V 50/60 Hz

• Power consumption: 5 W

• Luminous efficacy: 55 lm/W

• Power factor > 0,75

• THD: 26 %

• Photobiological hazard: Group 0

Inrush current - Ipeak: 5 A

• Peak duration - Twidth: 50 μs

• Fire resistance: 650 °C

 Number of luminaires on automat type B16: 50 pcs

• Weight: 1,1 kg

• Designed and made in France