
VENDOME MINI

80310102 VENDOME 100 2L B2C BRASS B B 500 CL1 MR Tubular wall light






- Tubular wall light VENDOME 100 2L (design: Normal Studio)
- Honeycomb perforation grid
- · Grid with BRASS finishing


Description

- Housing: Co-extruded polycarbonate/PMMA for inside/outside use
- End caps & fixing straps: 316L stainless steel brass finishing sensitive to scratches, handle • Gaskets: Gaskets moulded in EPDM with care
- Anodised aluminium reflector: BRASS
- Brass anodised aluminium grid inserted inside the housing
- External metal parts in 316L stainless steel and screws in A4 stainless steel
- Stainless steel gear tray with 2 porcelaine sockets E14



Light specifications and controlling

- With 2 clear LED E14 filament lamps (4W 2700K)
- non dimmable



Installation and maintenance

- Diameter: 100 mm
- Total length: 519 mm
- Provided with 1m 3G1,5 cable with tinned copper meshwork under transparent tubing
- Connection to 3x2.5mm² automatic terminal block
- 2 reinforced stainless Steel fixing straps (with variable centre distance) and allowing 360°
- Provided with stainless steel cable plate 316L, for indoor use (IP 40), for earthing
- · Installation in vertical position, cable gland positioned downwards



cd/klm C0 - C180 - - - C90 - C270











Characteristics

- Warranty: 5 years
- Operating temperature: -20 °C to +35 °C
- Protection: IP66/IP68/IP69K
- Resistance to IK shocks: IK10
- Electrical class: Class I

- Power supply: 220-240 V 50/60 Hz
- T°C with incandescent wires: 650°C
- Weight: 1,6 kg
- · Designed and made in France