

AIRMOD Trio

Triple pendant light





Conceived by the German designer Stefan Diez for Sammode, the AIRMOD Trio pendant light is the most majestic model in the AIRMOD collection. Each of the three heads, equipped with LED modules, is height-adjustable for great freedom of composition. With no visible power supply cable, this light and refined triple pendant light fitting will fit perfectly into any space thanks to its easy-to-install equipment housing. In a meeting room, opt for clear and diffuse lighting with its Silver version equipped with frosted shades.








Triple pendant light





Perforated collimator version

3 x 900 lm, 2700 K



Finishing	Endcap	Designation	Code	Watt
Silver	Silver	AIRMOD TRIO S 900-927 GR-S	88200075	39
Black	Black	AIRMOD TRIO BK 900-927 GR-BK	88200078	39
Champagne	Champagne	AIRMOD TRIO CH 900-927 GR-CH	88200028	39
Bronze	Bronze	AIRMOD TRIO BZ 900-927 GR-BZ	88200029	39

Frosted glass shade version

3 x 900 lm, 2700 K



Finishing	Endcap	Designation	Code Wa	att
Silver	Frosted	AIRMOD TRIO S 900-927 GL-FR	88200077 39)
Black	Frosted	AIRMOD TRIO BK 900-927 GL-FR	88200080 39)
Champagne	Frosted	AIRMOD TRIO CH 900-927 GL-FR	88200032 39)
Bronze	Frosted	AIRMOD TRIO BZ 900-927 GL-FR	88200033 39)

Glass version 3 x 900 lm, 2700 K



Finishing	Endcap	Designation	Code	Watt
Silver	Clear	AIRMOD TRIO S 900-927 GL-CL	88200076	39
Black	Green	AIRMOD TRIO BK 900-927 GL-GN	88200079	39
Champagne	Amber	AIRMOD TRIO CH 900-927 GL-AM	88200036	39
Bronze	Smoked	AIRMOD TRIO BZ 900-927 GL-SM	88200037	39

Options

Perforated collimator in anodised aluminium











Tempered glass shade





Color temperature	
2700K	927
3000K	930
4000K	940

RD

RB

Silver Black Champagne Bronze

GR-S GR-BK Green GR-CH Amber

Frosted Clear GR-BZ Smoked

GL-FR Lighting management GL-CL Electronic gear unit for DALI GL-GL GL-AM Casambi Bluetooth control





AIRMOD Trio Triple pendant light



Accessories










The interchangeable crowns and lenses can be ordered separately.

Specification






Photometry



Perforated collimator + Wide Beam Lens



Clear, frosted or tinted glass shade + Medium Beam Lens

- ·	
Design	
Designer	Stefan Diez
Technical characteristic	s
Light source	CoB LED Module 900 Im (without endcap, IRC>90, 3SDCM) 50 000 h L80/B10 at 25°C Photobiological hazard : Group 1
Control gear	Constant current driver (non-dimmable)
Supply voltage	220-240V 50/60Hz
Electrical class	Class I
Operating temperature	-5 °C to +35 °C
Easy intallation and main	ntenance
Connection	To a 3 x 2,5 mm² terminal block
Mounting	Power supply box for surface mounting
Hanging height	Suspension wires adjustable in height, up to 3 m.
Materials	
Head and device housing	Color anodizing Aluminium, nickel-plated copper hoop
Endcap	Perforated collimator: Color anodizing Aluminium Glass: clear, tinted or frosted tempered glass, according to versions
Lens	Tempered glass
Standards	
Waterproofness	IP20 (indoor use)
Fire resistance	850°C