

Bendz & Bendz SA

ø70 compact wall light



Bendz & Bendz SA

ø70 compact wall light






Bendz



Bendz SA

This small industrial wall light toys with transparency, to reveal its bulb, or else is dressed in a satin body, for the subtlest of lighting. As an occasional light, for use both indoors and out, the Bendz is ideal for lighting up a balcony, creating a mood on a facade, or as a bedside lamp in a bedroom.






Bendz & Bendz SA

ø70 compact wall light



Sammode






Bendz

Housing	Designation	Code
Claire	BENDZ 70 300 CL1 POME BCV	14415020

Bendz SA




Housing	Designation	Code
Satinée	BENDZ SA 70 300 CL1 POME BCV	14320020

Options

End caps & fixing straps finish	Fixing straps	Materials
	 	Coextruded polycarbonate/PMMA housing for Indoor/Outdoor use (650°) - Polycarbonate housing (960°C) PO End caps & fixing straps 304L stainless steel - End caps & fixing straps 316L stainless steel MR
End caps & straps painted Coal RAL7021	Fixing straps with HSHC screw COAL Fixing straps with tamper-resistant Torx screw	BCV BCVT

Accessories

To be ordered separately

		
Stainless steel cable plate kit (IP40) 17500020	Pre-cabing 1,5m 3G1.5 (3 wires) Braided tinned copper cable CAB0007	E27 LED filament lamp 4W 2700K matt 17500003 E27 LED filament lamp 8W 2700K matt 17500004



Bendz & Bendz SA

ø70 compact wall light




Sammode


Specification



Photometry



Bendz
ULR = 50%



Bendz SA
ULR = 50%

Technical characteristics	
Light source	E27 lamp, 11W max, not included
Supply voltage	220-240V 50/60Hz
Electrical class	Class I
Operating temperature	-20°C to +30°C
Easy intallation and maintenance	
Connection	With nickel-coated brass cable gland for cable Ø 5-12 mm To 3x2.5mm ² automatic terminal block Installation in vertical position: cable gland positioned downwards
Opening and closing	Closing by tightening the nut on the cable gland
Mounting	2 stainless steel fixing straps with HSHC screw (with variable centre distance)
Maintenance	By removal of the end cap with lampholder
Materials	
Housing	Coextruded polycarbonate/PMMA diameter 70 for indoor and outdoor use
End caps, fixing straps and gear unit cover	304L stainless steel
Standards	
Waterproofness	IP66, IP68, IP69K
Resistance to IK shocks	IK10
Fire resistance	650°C