

Bodom

Floor lamp



Sammode




The Bodom floor lamp is leaktight from top to bottom, and tough enough to withstand pretty much anything. Any indoor or outdoor area will look great bathed in its mellow lighting combined with its concrete base and aluminium mast. This sleek design with its metal slats is available in various colours to match your decor. This design is sober, timeless and long-lasting.



Bodom



Floor lamp



Floor lamp

Structure	Reflector	Flux (lm)	Designation	Code	Watt
● Coal	● Copper	700	BODOM 70 COAL COAL C 700 700-827 BPI CL1 CRC MR P1	80155112	12
	● Brass	700	BODOM 70 COAL COAL B 700 700-827 BPI CL1 CRB MR P1	80155113	12
	● Petrol	700	BODOM 70 COAL COAL P 700 700-827 BPI CL1 CRP MR P1	80155114	20
● Marsala	● Silver	700	BODOM 70 MARS MARS S 700 700-827 BPI CL1 CRS MR P1	80155115	12
○ White	● Brass	700	BODOM 70 WHITE WHITE B 700 700-827 BPI CL1 CRB MR P1	80155116	12

Options

Aluminium gear unit cover	Materials	Color temperature	
 	Coextruded polycarbonate/PMMA housing for Indoor/Outdoor use (650°)	2700K	827
	Polycarbonate housing (960°C)	3000K	830
		4000K	840
	PO	Lighting management	
Silver Copper Brass Petrol	CRS	Dimming by dim switch on cable	BPI
	CRC	Electronic gear unit for DALI dimming	RD
	CRB	Electronic gear unit for push button	RS
	CRP	Casambi Bluetooth control	RB
Electrical class			
Class I			CL1
Class II			-



Bodom

Floor lamp




Sammode

Specification



Photometry



Technical characteristics

Light source	High-efficiency removable LED module (CRI>80, 3 SDCM) 50 000 h L80/B10 at 25°C Photobiological hazard : None (RG0)
Optics	Specific satin-finish primary diffuser optics
Lighting comfort	Reflector with reversible longitudinal louvre in aluminum with inclined lamina
Control gear	Constant current driver, dimmable by dim switch on cable
Supply voltage	220-240V 50/60Hz
Electrical class	Class I
Operating temperature	-20°C to +30°C

Easy intallation and maintenance

Connection	Provided with 4 m 5G1,5 cable with tinned copper meshwork under transparent tubing with a european plug IP44
LED engine maintenance	Quick opening and closing with just one screw Maintenance without tampering with the cable by removal of the end cap without cable entry Close'N Connect Patented system with automatic electrical connection/disconnection on closure Easily removable LED modules and driver

Materials

Structure	Powder-coated aluminium with anti-corrosion treatment for outdoor use
Housing	Coextruded polycarbonate/PMMA diameter 70 for indoor and outdoor use
End caps and fixing straps	316L stainless steel

Standards

Waterproofness	IP66, IP68
Resistance to IK shocks	IK10
Fire resistance	650°C