






Thanks to its compact dimensions, the Gude wall light can fit in anywhere, both indoors and outdoors. This model was designed by Dominique Perrault and Gaëlle Lauriot-Prévost for Sammode, adding a classic timeless raw industrial feel to any decor. Thanks to its rectangular stainless steel louvre and diffuse 360° lighting, the Gude luminaire can create a cosy and mellow ambiance.









Gude



Wall light ø100



Gude

Finishing	Reflector	Designation	Code
 Inox	 Silver	GUDE 100 360° S 350 CL1	80300010
	 Coal	GUDE 100 360° COAL 350 CL1	80300003
 Coal	 Silver	GUDE 100 360° COAL S 350 CL1	80300004
	 Coal	GUDE 100 360° COAL COAL 350 CL1	80300005

Options

End caps & fixing straps finish	Fixing straps	Materials
 End caps & straps painted Coal RAL7021	 COAL Fixing straps Fixing straps with HSHC screw Fixing straps with tamper-resistant Torx screw	Coextruded polycarbonate/PMMA housing for Indoor/Outdoor use (650°) -
		Polycarbonate housing (960°C) PO
		End caps & fixing straps 304L stainless steel -
		End caps & fixing straps 316L stainless steel MR
		-
		BRV Lighting management
		Casambi Bluetooth control RB
		BRVT

Accessories

To be ordered separately

		
Stainless steel cable plate kit (IP40) 17500020	Pre-cabling 1,5m 3G1.5 (3 wires) Braided tinned copper cable CAB0007	E27 LED filament lamp 8W 2700K matt 17500004



Gude

Wall light ø100



Sammode

Specification



Design

Designer Dominique Perrault & Gaëlle Lauriot-Prévost

Technical characteristics

Light source E27 lamp, 11W max, not included

Supply voltage 220-240V 50/60Hz

Electrical class Class I

Operating temperature -20°C to +35°C

Easy intallation and maintenance

Connection With nickel-coated brass cable gland for cable Ø 5-14 mm
To 3x2.5mm² automatic terminal block
Installation in vertical position: cable gland positioned downwards

Opening and closing Opening by releasing the screw and extracting the diffuser

Mounting Attachement with 2 bolt-fitted stainless steel straps with variable center distance and 360° orientation

Materials

Internal grid Stainless steel grid

Housing Ø100 Co-extruded polycarbonate/PMMA for inside/outside use

End caps and fixing straps 304L stainless steel

Standards

Waterproofness IP66, IP68, IP69K

Resistance to IK shocks IK10

Fire resistance 650°C