






Whether you prefer the stainless steel finish or the colour version, the Musset wall light comes with a sober and yet elegant industrial design. Two filament LED bulbs are concealed in the glass body. The combination of a coloured reflector and multi-perforated louvres guarantees customisable subdued mellow lighting. This graphic Musset luminaire with its great design can be installed directly on walls or ceilings, or be suspended.



Musset

ø100 Wall light



With flux-breaker grid

Finishing	Reflector	Designation	Code
Inox	Silver	MUSSET GR 100 S 500 CL1 PY	15225077
	Copper	MUSSET GR 100 C 500 CL1 PY	15225073
Coal	Brass	MUSSET GR 100 COAL B 500 CL1 PY	15225084
	Petrol	MUSSET GR 100 COAL P 500 CL1 PY	15225085
Marsala	Silver	MUSSET GR 100 MARS S 500 CL1 PY	15225086
White	Brass	MUSSET GR 100 WHITE B 500 CL1 PY	15225087

Without flux-breaker grid

Finishing	Reflector	Designation	Code
Inox	Silver	MUSSET 100 S 500 CL1 PY	15225078
	Copper	MUSSET 100 C 500 CL1 PY	15225079
Coal	Brass	MUSSET 100 COAL B 500 CL1 PY	15225080
	Petrol	MUSSET 100 COAL P 500 CL1 PY	15225081
Marsala	Silver	MUSSET 100 MARS S 500 CL1 PY	15225082
White	Brass	MUSSET 100 WHITE B 500 CL1 PY	15225083

Options

End caps & fixing straps finish	Fixing straps	Materials
End caps & straps painted Coal RAL7021		End caps & fixing straps 304L stainless steel
End caps & straps painted MARSALA RAL3011		End caps & fixing straps 316L stainless steel
End caps & straps painted WHITE RAL9010		
	Fixing straps	-
	Fixing straps with HSHC screw	BRV
Reflector finish		
Silver	S	
Brass	B	
Copper	C	
Petrol	P	

Accessories

To be ordered separately



Stainless steel cable plate kit (IP40)	17500020	Pre-cabling 1,5m 3G1.5 (3 wires) Braided tinned copper cable	CAB0007	E14 LED filament lamp 4W 2700K clear	17500002
--	----------	--	---------	--------------------------------------	----------



Musset

ø100 Wall light



Sammode

Specification



Technical characteristics

Light source	2 E14 lamps, 11W max, not included
Supply voltage	220-240V 50/60Hz
Electrical class	Class I
Operating temperature	-20°C to +35°C

Easy intallation and maintenance

Connection	With nickel-coated brass cable gland for cable Ø 5-14 mm To a 3 x 2,5 mm ² disconnectable terminal block Installation in vertical position: cable gland positioned downwards
Mounting	Attachement with 2 bolt-fitted stainless steel straps with variable center distance and 360° orientation
Maintenance	Maintenance by releasing the 2 closing screws, removing the end cap and extracting the gear tray

Materials

Louvre	Stainless steel grid
Housing	Borosilicate-glass
End caps and fixing straps	304L stainless steel

Standards

Waterproofness	IP66, IP68, IP69K
Resistance to IK shocks	IK07
Fire resistance	Non-flammable