


The Rivoli luminaire was initially designed by Normal Studio for the Musée des Arts Décoratifs (Decorative arts museum) in Paris, but has managed to make the leap from contemporary art galleries to more traditional Sammode sites. This long and narrow elegant luminaire can be used for many applications. Whether installed on a wall or ceiling or as a suspended light fitting, either indoors or outdoors, this model lights up any space with the intricate patterns on the louvre.



Rivoli

ø100 Pendant light




Non dimmable

T (K)	Flux (lm)	L (mm)	Designation	Code	Watt
2700	1500	1318	RIVOLI 100 1300 1500-827 CL1 MR SUSP	80210021	25

Casambi dimmer



T (K)	Flux (lm)	L (mm)	Designation	Code	Watt
2700	1500	1318	RIVOLI 100 1300 1500-827 RB CL1 MR SUSP	80210014	25

Options

Fixing straps	Materials	Lighting management
	Coextruded polycarbonate/PMMA housing for Indoor/Outdoor use (650°) Polycarbonate housing (960°C)	Electronic gear unit for DALI 2 dimming - Casambi Bluetooth control PO
Fixing straps	-	
Fixing straps with HSHC screw	BRV	RD
Fixing straps with tamper-resistant Torx screw	BRVT	RB

Accessories

To be ordered separately

	
Stainless steel cable plate kit (IP40)	17500020
Pre-cabling 3m 3G1.5 (3 wires) Braided tinned copper cable	CAB0008
Pre-cabling 3m 5G1.5 (5 wires) Braided tinned copper cable	CAB0011



Rivoli

ø100 Pendant light




Sammode

Specification



Photometry



Design

Designer Normal Studio for the Musée des Arts Décoratifs, Paris

Technical characteristics

Light source High-efficiency removable LED module (CRI>80, 3 SDCM)
Color temperature 2700K
50 000 h L80/B10 at 25°C
Photobiological hazard : None (RG0)

Optics Specific satin-finish primary diffuser optics
Use of an internal film for a homogeneous light distribution

Lighting comfort Luminance control through diffusing optical systems

Control gear Constant current driver (non-dimmable)
Dimmable models : by Casambi bluetooth
Electronic compatible with central source

Supply voltage 220-240V ±10% 0/50/60Hz

Electrical class Class I

Operating temperature -20°C to +30°C

Easy intallation and maintenance

Connection With nickel-coated brass cable gland for cable Ø 5-14 mm
To a 3 x 2,5 mm² disconnectable terminal block

Opening and closing Quick, with just one screw

Mounting 2 stainless steel fixing straps (with variable centre distance)
Provided with 2 suspension kits and 3 m of steel wire

LED engine maintenance Patented sliding maintenance system
Easily removable LED modules and driver

Materials

Internal grid Painted steel grid

Housing Ø100 Co-extruded polycarbonate/PMMA for inside/outside use

End caps and fixing straps 316L stainless steel

Standards

Waterproofness IP66, IP68, IP69K

Resistance to IK shocks IK10

Fire resistance 650°C